## **PK081A**

## LED Light Pole Kit with Single Adjustable LED Light, Selectable Wattage 100/150/185 & Color Temperature, 10-25 Foot Pole Height Options



Job:		`	$\checkmark$	10-25 Foot Pole Height Options											ergy	B Light,	inc
Job Site:	State:	Client Name:													_		
Notes:		Approvals:							Date:								
Commercia Square steel I and hardware Light Pole: Pole Shaft: 4 commercial g Pole Height: 0 Custom heigh Anchor Bolts: Each anchor b Bolt Circle: 8- Handhole: Ha A 3" X 5" stee Color: Dark Bi Base Cover: A LED Fixture Material: Alui integrated fin Color: Dark Bi Preset Power Voltage: 120- Preset Color 1 Light Distribu Type 4 and Ty Photocell: Ph. Dimming: 0-1 Dimming cont ETL Listing: ET DLC Listing: D IP Rating: 1P6 EPA Rating: 0 Warranty: 5 Y Weight: 11.5	ight pole, is, set of an inch squar rade steel Optional hits are also A set of 4 polt including the formation of the formatio	Single LED schor bolts are 11 gaug with mini eights are available galvanize es 2 nuts a Circle ran located 18 e cover is i base cover is i base cover is i tandard.  Jure: 5000k as standard.  Jure: 5000k as specipitional.  Jure: Gapablovided (field or Wet Located 19 cover is in the second in the	light com and a base of (10 ft.,15 ft) distering and 2 washing ge: 8"-11" "above the included.  The with dissipation of discial order.  The control of the control of the control order.  The control of the control of the control order.  The control of the control of the control order.  The control of the control of the control order.  The control of	plete with e cover. ft. and 20 strength t, 20 ft. an chor bolts ners. ). ne base pla ets.	adjustabl 0 ft.) and 7 of 55,000 od 25 ft. is provide	e slip fitte 7 gauge (2 psi d.  4 90	Slots, — Apart		Slip F  Slip F  Sixture  View  Sixture  View  Sixture  View	stable		Pe He 100 155 20 25	hotocell Optional)			Pol	
POWER (W)	LOW			MID			HIGH					(0					
	100 0.87 @ 120V/0.38 @ 277V			150 1.31 @ 120V/0.57 @ 277V			185 1.62 @ 120V/0.70 @ 277V			18"			<sup>–</sup> 2-Piece Base Co	ver			
COLOR TEMPERATURE	3000 4000 5000		3000 4000		5000	3000	4000	5000			- I /	Base Plate	<u> </u>			_	
(K) LUMENS	14,500	16,000	15,000	21,750	24,000	22,500	26,825	29,600	27,750				3.75" Bolt		. <del></del>		
LUMENS/WATT	145	160	150	145	160	150	145	160	150			Pi	rojection				
<b>Disclaimer:</b> All dimensi											· · · · · · · · · · · · · · · · · · ·	A	nchor Bol	lt	· · · · · · · · · · · · · · · · · · ·		

Copyright© 2023 Energy Light, Inc. All Rights Reserved | 1881 Rose Road, Lake Zurich, IL 60047